



CHILL OUT

FREEZING PENETRATING LUBRICANT

DESCRIPTION

CHILL OUT combines rapid freezing and a special penetrating lubricant to easily loosen bound parts. Sprayed areas shrink and create openings to allow the lubricant to penetrate and open up the toughest bonds.

APPLICATIONS

Liberal application will loosen threads, tightened fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. The formula will protect against renewed corrosion.

FEATURES & BENEFITS

- Freezing Action Unlocks Rusted Parts
- Nonconductive
- Low VOC Content
- Nonchlorinated

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Ketone
COLOR: Hazy White
DETERGENCY: None
TOXICITY: 50 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year plus
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.91
% VOLATILE BY VOLUME: 83.5%
pH: N/A
PROPELLANT: Difluoroethane
EVAPORATION RATE: Moderate
BIODEGRADABILITY: No

LABEL INFORMATION

CHILL OUT FREEZING PENETRATING LUBRICANT

CHILL OUT combines rapid freezing and a special penetrating lubricant to easily loosen bound parts. Sprayed areas shrink and create openings to allow the lubricant to penetrate and open up the toughest bonds.

TO LOOSEN BOUND PARTS: Liberal application will loosen threads, tightened fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. The formula will protect against renewed corrosion.


DIRECTIONS FOR USE: Shake well before using. Insert extension tube into valve opening and spray liberally on surface to be treated. Concentrate spray on part to be loosened and avoid the surrounding surfaces. Part should be ready to loosen or remove after waiting about 30 seconds. Repeat if required.

NOTE: Sudden drop in temperature after spraying may result in cracking of some paint and plastic. Test first in an inconspicuous area.

DANGER: FLAMMABLE. Contains 1,1-Difluoroethane and Methyl Isobutyl Ketone. Contents under pressure. Use only in well ventilated area. Vapors may accumulate and ignite in enclosed areas. Do not use near fire or open flame. Do not puncture. Do not store above 120°F. Do not throw container into fire or incinerator. Eye and skin irritant. Avoid frequent or prolonged contact with skin. Contact with skin may cause frostbite. If skin blisters, contact physician immediately. Avoid contact with eyes. If in eyes, flush thoroughly with water for at least 15 minutes and contact physician if irritation persists. If swallowed, do not induce vomiting. Contact physician immediately.

CONTAINS (CAS#): 1,1-Difluoroethane (75-37-6), Polysiloxane (63148-62-9), Methyl Isobutyl Ketone (108-10-1), Tall Oil Fatty Acid (61790-12-3).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	A



PACKAGING INFORMATION

12 - 16 oz cans per case, 9 oz net weight